

# SPECIFICATION SHEET

**GALUX** PRO



## LED Down Light Nuvio



### Technical Characteristics

Nominal Power	Size A: 10W Size B: 20W
Lumen (Efficacy)	110 LM/W
LED Type	PHILIPS COB
CCT	3000°K-6000°K
CRI	>80
Beam Angle	60°
Protection	IP20 / IP44
Operation Temp.	0 to 45°C
Dimension	A: Ø108*H54mm B: Ø180*H60mm
Mounting	Recessed
Warranty	3 - 5 years

### Electrical Characteristics

Power Supply	LED Driver (Philips)
Voltage Range	220-240Vac
Power Factor	>0.95
Current (RMS)	0.048A / 0.095

### Materials

Body	Die-Casted Alu
Emitting surface	Polycarbonate

Code	Type	CCT
Nuvio108.10.K30.--	LED Down light Recessed 10W	3000K
Nuvio108.10.K40.--	LED Down light Recessed 10W	4000K
Nuvio108.10.K60.--	LED Down light Recessed 10W	6000K
Nuvio180.20.K30.--	LED Down light Recessed 20W	3000K
Nuvio180.20.K40.--	LED Down light Recessed 20W	4000K
Nuvio180.20.K60.--	LED Down light Recessed 20W	6000K